



NAUTILUS® ReFresh is produced with the TRIOTEC® 3-layer sandwich technology and offers a unique environmental profile: 70% TCF (Totally Chlorine Free) virgin fibre in the outer layers + 30% recycled fibre in the middle + FSC® certified. Perfect runnability thanks to increased stiffness for “stress-free” high volume print jobs, BLI guaranteed.



**Technical Data:** NAUTILUS® ReFresh TRIOTEC

<b>Basis weight</b>	g/m <sup>2</sup>	ISO 536	<b>80 ± 3.0</b>
<b>Caliper</b>	µm	ISO 534	<b>106 ± 3</b>
<b>Bulk</b>	cm <sup>3</sup> /g	ISO 534	<b>1.3</b>
<b>Opacity</b>	%	ISO 2471	<b>92.5</b>
<b>Moisture abs.</b>	%	ISO 287	<b>4.6 ± .5</b>
<b>Brightness UV</b>	%	ISO 2470	<b>110.0 ± 1.5</b>
<b>CIE Whiteness</b>	%	ISO 11475	<b>161 ± 3.0</b>
<b>Curve/Flatness</b>		<b>max</b>	<b>30</b>

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper. Production processes certified according to ISO 9001, ISO 14001 and OHSAS 18001. Standard measurement uncertainty between laboratories is not incorporated.

SIGNIFICANCE OF VALUES: 2 SIGMA