

Current version: 3.1.0, issued: 03.06.2019 Replaced version: 3.0.0, issued: 03.06.2019 Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name

edding Paint Marker Ink (silver) contained in: edding 790A, edding 791A, edding 792A paint marker

Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses of the substance or mixture

Ink for use in felt pens

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

+49 (0) 41 02 / 80 8-0 Telephone no.

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 **Emergency telephone number**

For medical advice (in German and English): +49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Asp. Tox. 1; H304 Flam. Liq. 2; H225 Skin Irrit. 2; H315 **STOT SE 3: H336**

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02







Signal word Danger



Trade name: edding Paint Marker Ink (silver) contained in: edding 790A, edding 791A, edding 792A paint m

Current version: 3.1.0, issued: 03.06.2019 Reglaced version: 3.0.0, issued: 03.06.2019 Region: GB

Hazardous component(s) to be indicated on label:

ETHYLCYCLOHEXANE

Hydrocarbons, C7-C9, Isoalkanes

Hazard statement(s)

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.

P391 Collect spillage. P405 Store locked up.

P501 Dispose of contents/container to a facility in accordance with local and national

regulations.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Chemical characterization

Mixture (preparation)



Current version: 3.1.0, issued: 03.06.2019 Reglaced version: 3.0.0, issued: 03.06.2019 Region: GB

Hazardous ingredients

No	Substance name		Additional information		
NO		01 1/1 (1 (70) (000) (01 0)			0.1
	CAS / EC / Index /	Classification (EC) 1272/2008 (CLP)	Concentration		%
	REACH no				
1	ETHYLCYCLOHEXANE				
	1678-91-7	Flam. Liq. 2; H225	>= 25.00 - < 50	0.00	%-b.w.
	216-835-0	Aquatic Chronic 2; H411			
	-	STOT SE 3; H336			
	01-2120769125-	Aquatic Acute 1; H400			
	52-0000	Asp. Tox. 1; H304			
2	Hydrocarbons, C7-				
	-	Aquatic Chronic 2; H411	>= 10.00 - < 25	5.00	%-b.w.
	921-728-3	Asp. Tox. 1; H304			
	-	Flam. Liq. 2; H225			
	01-2119471305-	Skin Irrit. 2; H315			
	42-0010	STOT SE 3; H336			
3	aluminium powder	(stabilised)			
	7429-90-5	Flam. Sol. 1; H228	>= 10.00 - < 25	5.00	%-b.w.
	231-072-3	Water-react. 2; H261			
	013-002-00-1	, ,			
	-				
4	Solvent naphtha (p	etroleum), light arom.	Enthält < 0,1 Gew%		
	,		Benzol.		
	64742-95-6	Aquatic Chronic 2; H411	>= 5.00 - < 10	0.00	%-b.w.
	265-199-0	Asp. Tox. 1; H304			
	649-356-00-4	Flam. Liq. 3; H226			
	-	Skin Irrit. 2; H315			
		STOT SE 3; H336			
	T . (151111111111111111111111111111111111111			

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
3	Т	-	-	-
4	Р	-	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Rinse mouth thoroughly with water. Call a doctor immediately. Never give anything by mouth to an unconscious person.



Current version: 3.1.0, issued: 03.06.2019 Reglaced version: 3.0.0, issued: 03.06.2019 Region: GB

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO2); Carbon monoxide (CO); Nitrogen oxides (NOx); Toxic gases/vapours

5.3 Advice for firefighters

Use self-contained breathing apparatus. Cool endangered containers with water spray jet. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away sources of ignition.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When picked up, treat material as prescribed under heading "Disposal considerations".

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far it is possible by the state of the art.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Provide eye wash fountain in work area. Have emergency shower available.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight.



Current version: 3.1.0, issued: 03.06.2019 Reglaced version: 3.0.0, issued: 03.06.2019 Region: GB

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

Advice on storage assembly

Do not store together with: Bases; Acids; oxidizing agents

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.		EC no.
1	aluminium powder (stabilised)	7429-90-5		231-072-3
	List of approved workplace exposure limits (WELs) / E	H40		
	Aluminium metal			
	total inhalable dust			
	WEL long-term (8-hr TWA reference period)	10	mg/m³	
	List of approved workplace exposure limits (WELs) / E	H40		
	Aluminium metal			
	respirable dust	•		
	WEL long-term (8-hr TWA reference period)	4	mg/m³	

DNEL, DMEL and PNEC values

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Туре	Value	
1	ETHYLCYCLOHEXANE		1678-91-7 216-835-0	
	water	fresh water	0.63	μg/L
	water	marine water	63	ng/L
	water	Aqua intermittent	6.3	μg/L
	water	fresh water sediment	0.573	mg/kg dry weight
	water	marine water sediment	57.3	μg/kg dry weight
	soil	-	0.114	mg/kg dry weight
	sewage treatment plant	-	32	mg/L

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)



Trade name: edding Paint Marker Ink (silver) contained in: edding 790A, edding 791A, edding 792A paint m

Current version: 3.1.0, issued: 03.06.2019 Reglaced version: 3.0.0, issued: 03.06.2019 Region: GB

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form/Colour		
liquid		
silver coloured		
Odour		
characteristic		
Odour threshold		
No data available		
pH value		
No data available		
Boiling point / boiling range		
No data available		
Melting point / melting range		
No data available		
Decomposition point / decomposition range		
No data available		
Flash point		
Value	7	°C



Trade name: edding Paint Marker Ink (silver) contained in: edding 790A, edding 791A, edding 792A paint m

Current version: 3.1.0, issued: 03.06.2019 Reglaced version: 3.0.0, issued: 03.06.2019 Region: GB

Auto-	ianition	temperature

No data available

Oxidising properties

No data available

Explosive properties

No data available

Flammability (solid, gas)

No data available

Lower flammability or explosive limits

No data available

Upper flammability or explosive limits

No data available

Vapour pressure

No data available

Vapour density

No data available

Evaporation rate

No data available

Relative density

No data available

Density

Value 1.03 g/cm³
Reference temperature 20 °C

Solubility in water

Comments insoluble

Solubility(ies)

No data available

Partition coefficient: n-octanol/water

No data available

|--|

Value	16.0 mm²/s
Reference temperature	40 °C
Туре	kinematic

9.2 Other information

Other information

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.



Trade name: edding Paint Marker Ink (silver) contained in: edding 790A, edding 791A, edding 792A paint m

Current version: 3.1.0, issued: 03.06.2019 Reglaced version: 3.0.0, issued: 03.06.2019 Region: GB

10.5 Incompatible materials

Bases; Acids; Oxidizing agents

10.6 Hazardous decomposition products

Nitrous oxides (NOx)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acu	Acute oral toxicity						
No	Substance name		CAS no.		EC no.		
1	Hydrocarbons, C7-C9, Isoalkanes		-		921-728-3		
LD5	0	>		2000	mg/kg bodyweight		
Spe	cies	rat					
Meth	nod	OECD 401					
Sou	rce	ECHA					

Acu	Acute dermal toxicity					
No	Substance name		CAS no.		EC no.	
1	Hydrocarbons, C7-C9, Isoalkanes		-		921-728-3	
LD5	0	>	2	2000	mg/kg bodyweight	
Spe	cies	rabbit				
Soul	rce	ECHA				

Acute inhalational toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Reproduction toxicity

No data available

Carcinogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation of vapours may lead to headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.



Current version: 3.1.0, issued: 03.06.2019 Replaced version: 3.0.0, issued: 03.06.2019 Region: GB

SECTION 12: Ecological information

12.1 Toxicity

Toxi	exicity to fish (acute)					
No	Substance name	CAS no.		EC no.		
1	ETHYLCYCLOHEXANE	1678-91-7		216-835-0		
LC5	0		0.75	mg/l		
Dura	ation of exposure		96	h		
Spec	cies	Oryzias latipes				
Meth	nod	OECD 203				
Soul	ce	CSR				
2	Hydrocarbons, C7-C9, Isoalkanes	-		921-728-3		
LL50			18.4	mg/l		
Dura	ation of exposure		96	h		
Spec	cies	Oncorhynchus mykiss				
Method		OECD 203				
Soul	rce	ECHA				

Tox	Toxicity to fish (chronic)						
No	Substance name	CAS no.		EC no.			
1	Hydrocarbons, C7-C9, Isoalkanes	-		921-728-3			
NOELR			0.778	mg/l			
Dura	ation of exposure		28	day(s)			
Spe	cies	Oncorhynchus mykiss					
Method		(Q)SAR					
Sou	rce	ÉCHA					

Tox	Toxicity to Daphnia (acute)				
No	Substance name	CAS no.		EC no.	
1	ETHYLCYCLOHEXANE	1678-91-7		216-835-0	
EC5	0		0.667	mg/l	
Dura	ation of exposure		48	h	
Spe	cies	Daphnia magna			
Method		OECD 202			
Sou	rce	CSR			
2	Hydrocarbons, C7-C9, Isoalkanes	-		921-728-3	
EL5	0	appr.	2.4	mg/l	
Dura	ation of exposure		48	h	
Spe	cies	Daphnia magna			
Sou	rce	ECHA			

Toxicity to Daphnia (chronic) No data available

Tox	Toxicity to algae (acute)				
No	Substance name	CAS no.		EC no.	
1	ETHYLCYCLOHEXANE	1678-91-7		216-835-0	
EC5	0		0.633	mg/l	
Duration of exposure			72	h	
Species		Pseudokirchneriella subcapi	tata		
Method		OECD 201	OECD 201		
Source		CSR			

Tox	Toxicity to algae (chronic)				
No	Substance name	CAS no.		EC no.	
1	ETHYLCYCLOHEXANE	1678-91-7		216-835-0	
NOEC			0.22	mg/l	
Duration of exposure			72	h ¯	
Species		Algae			



Trade name: edding Paint Marker Ink (silver) contained in: edding 790A, edding 791A, edding 792A paint m

Current version: 3.1.0, issued: 03.06.2019 Reglaced version: 3.0.0, issued: 03.06.2019 Region: GB

Bacteria toxicity
No data available

12.2 Persistence and degradability

Biod	Biodegradability				
No	Substance name	CAS no.		EC no.	
1	ETHYLCYCLOHEXANE	1678-91-7		216-835-0	
Valu	ie		0	%	
Dura	ation		28	day(s)	
Method		OECD 301 C			
Source		CSR			
Evaluation		not readily biodegradable			

12.3 Bioaccumulative potential

Biod	Bioconcentration factor (BCF)				
No	Substance name	CAS no.		EC no.	
1	ETHYLCYCLOHEXANE	1678-91-7	'	216-835-0	
BCF		474	- 83	9	
Method		QSAR			
Source		CSR			

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

No data available.

12.7 Other information

Other	r information
Do no	ot discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class 3 Classification code F1 Packing group Ш Hazard identification no. 33 **UN** number UN1263 Proper shipping name **PAINT** 640D Special Provision 640 Tunnel restriction code D/E Label

Environmentally hazardous

substance mark

Symbol "fish and tree"



Trade name: edding Paint Marker Ink (silver) contained in: edding 790A, edding 791A, edding 792A paint m

Current version: 3.1.0, issued: 03.06.2019 Reglaced version: 3.0.0, issued: 03.06.2019 Region: GB

14.2 Transport IMDG

Class 3
Packing group II
UN number UN1263
Proper shipping name PAINT

Technical name ETHYLCYCLOHEXANE

Hydrocarbons, C7-C9, Isoalkanes

EmS F-E, S-E Label 3

Marine pollutant mark Symbol "fish and tree"

14.3 Transport ICAO-TI / IATA

Class 3
Packing group II
UN number UN1263
Proper shipping name Paint
Label 3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annexe No 3, 40 XVII.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:

F1 P5h

If the properties of the substance/product give rise to more than one classification, for the purposes of 2012/18/UE, the lowest qualifying quantities set out in Part 1 and Part 2 of Annex I shall apply.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.



Current version: 3.1.0, issued: 03.06.2019 Reglaced version: 3.0.0, issued: 03.06.2019 Region: GB

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H226 Flammable liquid and vapour.

H228 Flammable solid.

H261 In contact with water releases flammable gases.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

This substance may be marketed in a form which does not have the physical hazards as

indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s)

shall be included in the safety data sheet.

P The classification as a carcinogen or mutagen need not apply if it can be shown that the

substance contains less than 0.1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

Department issuing safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH. Prod-ID 636286