

Trade name: edding OHP-Ink Permanent (green) contained in: edding 140 S, edding 141 F, edding

Current version : 4.2.0, issued: 21.01.2020

Replaced version: 4.1.0, issued: 20.06.2018

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

edding OHP-Ink Permanent (green) contained in: edding 140 S, edding 141 F, edding 142 M, edding 143 B, edding 147 S, edding 148 F und edding 149 M

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Ink for use in felt pens

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 2; H225

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07

Signal word

Danger

Hazardous component(s) to be indicated on label:

1-methoxy-2-propanol

Hazard statement(s)

Trade name: edding OHP-Ink Permanent (green) contained in: edding 140 S, edding 141 F, edding

Current version : 4.2.0, issued: 21.01.2020

Replaced version: 4.1.0, issued: 20.06.2018

Region: GB

| | |
|-----------------------------------|--|
| H225 | Highly flammable liquid and vapour. |
| H336 | May cause drowsiness or dizziness. |
| Precautionary statement(s) | |
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P370+P378 | In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish. |
| P405 | Store locked up. |
| P501 | Dispose of contents/container to a facility in accordance with local and national regulations. |

2.3 Other hazards
No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Chemical characterization

Mixture (preparation)

Hazardous ingredients

| No | Substance name | | Additional information | |
|----|--|---|------------------------|--------|
| | CAS / EC / Index / REACH no | Classification (EC) 1272/2008 (CLP) | Concentration | % |
| 1 | 1-methoxy-2-propanol | | | |
| | 107-98-2 203-539-1 603-064-00-3 01-2119457435-35-0034 | Flam. Liq. 3; H226 STOT SE 3; H336 | >= 50.00 - < 70.00 | %-b.w. |
| 2 | ethanol | | | |
| | 64-17-5 200-578-6 603-002-00-5 01-2119457610-43 | Flam. Liq. 2; H225 | >= 10.00 - < 25.00 | %-b.w. |
| 3 | propan-2-ol | | | |
| | 67-63-0 200-661-7 603-117-00-0 01-2119457558-25-0085 | Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336 | >= 5.00 - < 10.00 | %-b.w. |

Full Text for all H-phrases and EUH-phrases: pls. see section 16

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Trade name: edding OHP-Ink Permanent (green) contained in: edding 140 S, edding 141 F, edding

Current version : 4.2.0, issued: 21.01.2020

Replaced version: 4.1.0, issued: 20.06.2018

Region: GB

Wash immediately with plenty of water for several minutes.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Rinse mouth thoroughly with water. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam; Extinguishing powder; Carbon dioxide

Unsuitable extinguishing media

No data available.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Cool endangered containers with water spray jet. Wear protective clothing. Suppress gases/vapours/mists with water spray jet.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away sources of ignition.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When collected, handle material as described under the section heading "Disposal considerations".

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Provide eye wash fountain in work area. Have emergency shower available.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from

Trade name: edding OHP-Ink Permanent (green) contained in: edding 140 S, edding 141 F, edding

Current version : 4.2.0, issued: 21.01.2020

Replaced version: 4.1.0, issued: 20.06.2018

Region: GB

sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

| No | Substance name | CAS no. | EC no. |
|----|---|------------------------|------------------|
| 1 | 1-methoxy-2-propanol | 107-98-2 | 203-539-1 |
| | 2000/39/EC | | |
| | 1-Methoxypropanol-2 | | |
| | WEL short-term (15 min reference period) | 568 mg/m ³ | 150 ppm |
| | WEL long-term (8-hr TWA reference period) | 375 mg/m ³ | 100 ppm |
| | Skin resorption / sensibilisation | Skin | |
| | List of approved workplace exposure limits (WELs) / EH40 | | |
| | 1-Methoxypropan-2-ol | | |
| | WEL short-term (15 min reference period) | 560 mg/m ³ | 150 ppm |
| | WEL long-term (8-hr TWA reference period) | 375 mg/m ³ | 100 ppm |
| | Comments | Sk | |
| 2 | ethanol | 64-17-5 | 200-578-6 |
| | List of approved workplace exposure limits (WELs) / EH40 | | |
| | Ethanol | | |
| | WEL long-term (8-hr TWA reference period) | 1920 mg/m ³ | 1000 ppm |
| 3 | propan-2-ol | 67-63-0 | 200-661-7 |
| | List of approved workplace exposure limits (WELs) / EH40 | | |
| | Propan-2-ol | | |
| | WEL short-term (15 min reference period) | 1250 mg/m ³ | 500 ppm |
| | WEL long-term (8-hr TWA reference period) | 999 mg/m ³ | 400 ppm |

DNEL, DMEL and PNEC values

DNEL values (worker)

| No | Substance name | | | CAS / EC no | |
|----|-----------------------------|---------------------|----------|-------------------------------------|-------------------|
| | Route of exposure | Exposure time | Effect | Value | |
| 1 | 1-methoxy-2-propanol | | | 107-98-2 203-539-1 | |
| | dermal | Long term (chronic) | systemic | 50.6 | mg/kg/day |
| | inhalative | Long term (chronic) | systemic | 369 | mg/m ³ |
| | inhalative | Short term (acut) | local | 553.5 | mg/m ³ |
| 2 | ethanol | | | 64-17-5 200-578-6 | |
| | dermal | Long term (chronic) | systemic | 343 | mg/kg/day |
| | inhalative | Long term (chronic) | systemic | 950 | mg/m ³ |
| | inhalative | Short term (acut) | local | 1900 | mg/m ³ |
| 3 | propan-2-ol | | | 67-63-0 200-661-7 | |
| | dermal | Long term (chronic) | systemic | 888 | mg/kg/day |
| | inhalative | Long term (chronic) | systemic | 500 | mg/m ³ |

DNEL value (consumer)

Trade name: edding OHP-Ink Permanent (green) contained in: edding 140 S, edding 141 F, edding

Current version : 4.2.0, issued: 21.01.2020

Replaced version: 4.1.0, issued: 20.06.2018

Region: GB

| No | Substance name | | | CAS / EC no | |
|----|-----------------------------|---------------------|----------|-------------------------------------|-------------------|
| | Route of exposure | Exposure time | Effect | Value | |
| 1 | 1-methoxy-2-propanol | | | 107-98-2 203-539-1 | |
| | oral | Long term (chronic) | systemic | 3.3 | mg/kg/day |
| | dermal | Long term (chronic) | systemic | 18.1 | mg/kg/day |
| | inhalative | Long term (chronic) | systemic | 43.9 | mg/m ³ |
| 2 | ethanol | | | 64-17-5 200-578-6 | |
| | oral | Long term (chronic) | systemic | 87 | mg/kg/day |
| | dermal | Long term (chronic) | systemic | 206 | mg/kg/day |
| | inhalative | Short term (acut) | local | 950 | mg/m ³ |
| 3 | propan-2-ol | | | 67-63-0 200-661-7 | |
| | oral | Long term (chronic) | systemic | 26 | mg/kg/day |
| | dermal | Long term (chronic) | systemic | 319 | mg/kg/day |
| | inhalative | Long term (chronic) | systemic | 89 | mg/m ³ |

PNEC values

| No | Substance name | | CAS / EC no | | |
|-------------------------|-------------------------------|-----------------------|-------------------------------------|-------|------|
| | ecological compartment | Type | Value | | |
| 1 | 1-methoxy-2-propanol | | 107-98-2 203-539-1 | | |
| | water | fresh water | 10 | mg/L | |
| | water | marine water | 1 | mg/L | |
| | water | Aqua intermittent | 100 | mg/L | |
| | water | fresh water sediment | 52.3 | mg/kg | |
| | with reference to: dry weight | | | | |
| | water | marine water sediment | 5.2 | mg/kg | |
| | with reference to: dry weight | | | | |
| | soil | - | 5.49 | mg/kg | |
| | with reference to: dry weight | | | | |
| sewage treatment plant | | - | 100 | mg/L | |
| 2 | ethanol | | 64-17-5 200-578-6 | | |
| | water | fresh water | 0.96 | mg/L | |
| | water | marine water | 0.79 | mg/L | |
| | water | fresh water sediment | 3.6 | mg/kg | |
| | with reference to: dry weight | | | | |
| | water | Aqua intermittent | 2.75 | mg/L | |
| | soil | - | 0.63 | mg/kg | |
| | with reference to: dry weight | | | | |
| | sewage treatment plant | | - | 580 | mg/L |
| | secondary poisoning | | - | 0.72 | g/kg |
| with reference to: food | | | | | |
| 3 | propan-2-ol | | 67-63-0 200-661-7 | | |
| | water | fresh water | 140.9 | mg/L | |
| | water | marine water | 140.9 | mg/L | |
| | water | fresh water sediment | 552 | mg/L | |
| | water | marine water sediment | 552 | mg/L | |
| | water | Aqua intermittent | 140.9 | | |
| | soil | - | 28 | mg/kg | |
| | sewage treatment plant | | - | 2251 | mg/L |
| secondary poisoning | | - | 160 | mg/kg | |
| with reference to: food | | | | | |

8.2 Exposure controls

Trade name: edding OHP-Ink Permanent (green) contained in: edding 140 S, edding 141 F, edding

Current version : 4.2.0, issued: 21.01.2020

Replaced version: 4.1.0, issued: 20.06.2018

Region: GB

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|-------------|
| Form/Colour | |
| liquid | |
| green | |
| Odour | |
| weak | |
| Odour threshold | |
| No data available | |
| pH value | |
| No data available | |
| Boiling point / boiling range | |
| Value | 78 °C |
| Reference substance | CAS 64-17-5 |
| Melting point / melting range | |
| No data available | |
| Decomposition point / decomposition range | |
| No data available | |
| Flash point | |
| Value | 13 °C |
| Reference substance | CAS 64-17-5 |
| Auto-ignition temperature | |
| No data available | |
| Oxidising properties | |
| No data available | |
| Explosive properties | |
| No data available | |
| Flammability (solid, gas) | |
| No data available | |

Trade name: edding OHP-Ink Permanent (green) contained in: edding 140 S, edding 141 F, edding

Current version : 4.2.0, issued: 21.01.2020

Replaced version: 4.1.0, issued: 20.06.2018

Region: GB

| | | | |
|---|-----------------------|----------------|---------------|
| Lower flammability or explosive limits | | | |
| Value | 1.9 | % vol | |
| Upper flammability or explosive limits | | | |
| Value | 13.1 | % vol | |
| Vapour pressure | | | |
| No data available | | | |
| Vapour density | | | |
| No data available | | | |
| Evaporation rate | | | |
| No data available | | | |
| Relative density | | | |
| Value | 0.953 | | |
| Density | | | |
| No data available | | | |
| Solubility in water | | | |
| Comments | insoluble | | |
| Solubility(ies) | | | |
| No data available | | | |
| Partition coefficient: n-octanol/water | | | |
| No | Substance name | CAS no. | EC no. |
| 1 | propan-2-ol | 67-63-0 | 200-661-7 |
| log Pow | | 0.05 | |
| Reference temperature | | 25 | °C |
| Source | ECHA | | |
| Viscosity | | | |
| No data available | | | |

9.2 Other information

| |
|--------------------------|
| Other information |
| No data available. |

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

Heat; air humidity

10.5 Incompatible materials

No data available.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Trade name: edding OHP-Ink Permanent (green) contained in: edding 140 S, edding 141 F, edding

Current version : 4.2.0, issued: 21.01.2020

Replaced version: 4.1.0, issued: 20.06.2018

Region: GB

| Acute oral toxicity | | | |
|---------------------------|---|----------|------------------|
| No | Substance name | CAS no. | EC no. |
| 1 | 1-methoxy-2-propanol | 107-98-2 | 203-539-1 |
| LD50 | | 4016 | mg/kg bodyweight |
| Species | rat | | |
| Method | EC 440/2008, B.1 | | |
| Source | ECHA | | |
| 2 | ethanol | 64-17-5 | 200-578-6 |
| LD50 | | 10740 | mg/kg bodyweight |
| Species | rat | | |
| Method | OECD 401 | | |
| Source | ECHA | | |
| 3 | propan-2-ol | 67-63-0 | 200-661-7 |
| LD50 | | 5840 | mg/kg bodyweight |
| Species | rat | | |
| Method | OECD 401 | | |
| Source | ECHA | | |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |

| Acute dermal toxicity | | | |
|-----------------------|----------------------|----------|------------------|
| No | Substance name | CAS no. | EC no. |
| 1 | 1-methoxy-2-propanol | 107-98-2 | 203-539-1 |
| LD50 | > | 2000 | mg/kg bodyweight |
| Species | rat | | |
| Method | 440/2008/EC B.3. | | |
| Source | ECHA | | |

| Acute inhalational toxicity | | | |
|-----------------------------|---|---------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | ethanol | 64-17-5 | 200-578-6 |
| LC50 | | 124.7 | mg/l |
| Duration of exposure | | 4 | h |
| State of aggregation | Dust/mist | | |
| Species | rat | | |
| Method | OECD 403 | | |
| Source | ECHA | | |
| 2 | propan-2-ol | 67-63-0 | 200-661-7 |
| LC50 | > | 10000 | ppmV |
| Duration of exposure | | 6 | h |
| State of aggregation | Gas | | |
| Species | rat | | |
| Method | OECD 403 | | |
| Source | ECHA | | |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |

| Skin corrosion/irritation | | | |
|---------------------------|---|----------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | 1-methoxy-2-propanol | 107-98-2 | 203-539-1 |
| Species | rabbit | | |
| Method | EC 440/2008, B.4 | | |
| Source | ECHA | | |
| Evaluation | non-irritant | | |
| 2 | propan-2-ol | 67-63-0 | 200-661-7 |
| Species | rabbit | | |
| Source | ECHA | | |
| Evaluation | non-irritant | | |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |

| Serious eye damage/irritation | | | |
|-------------------------------|----------------------|----------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | 1-methoxy-2-propanol | 107-98-2 | 203-539-1 |
| Species | rabbit | | |

Trade name: edding OHP-Ink Permanent (green) contained in: edding 140 S, edding 141 F, edding

Current version : 4.2.0, issued: 21.01.2020

Replaced version: 4.1.0, issued: 20.06.2018

Region: GB

| | | | |
|---------------------------|---|----------------|------------------|
| Method | 2004/73/EEC, B.5 | | |
| Source | ECHA | | |
| Evaluation | non-irritant | | |
| 2 | propan-2-ol | 67-63-0 | 200-661-7 |
| Species | rabbit | | |
| Method | OECD 405 | | |
| Source | ECHA | | |
| Evaluation | irritant | | |
| Evaluation/classification | Based on available data, the classification criteria are met. | | |

| Respiratory or skin sensitisation | | | |
|--|---|-----------------|------------------|
| No | Substance name | CAS no. | EC no. |
| 1 | 1-methoxy-2-propanol | 107-98-2 | 203-539-1 |
| Route of exposure | | Skin | |
| Species | guinea pig | | |
| Method | 440/2008/EC B.6 | | |
| Source | ECHA | | |
| Evaluation | non-sensitizing | | |
| 2 | ethanol | 64-17-5 | 200-578-6 |
| Route of exposure | | Skin | |
| Species | mouse | | |
| Method | OECD 429 | | |
| Source | ECHA | | |
| Evaluation | non-sensitizing | | |
| 3 | propan-2-ol | 67-63-0 | 200-661-7 |
| Route of exposure | | Skin | |
| Species | guinea pig | | |
| Method | OECD 406 | | |
| Source | ECHA | | |
| Evaluation | non-sensitizing | | |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |

| Germ cell mutagenicity | | | |
|-------------------------------|--------------------|---|------------------|
| No | Substance name | CAS no. | EC no. |
| 1 | ethanol | 64-17-5 | 200-578-6 |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |
| 2 | propan-2-ol | 67-63-0 | 200-661-7 |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |

| Reproduction toxicity | | | |
|------------------------------|----------------|---|------------------|
| No | Substance name | CAS no. | EC no. |
| 1 | ethanol | 64-17-5 | 200-578-6 |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |

| Carcinogenicity | | | |
|---------------------------|----------------|---|------------------|
| No | Substance name | CAS no. | EC no. |
| 1 | ethanol | 64-17-5 | 200-578-6 |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |

| STOT - single exposure | |
|-------------------------------|--|
| No data available | |

| STOT - repeated exposure | |
|---------------------------------|--|
| No data available | |

| Aspiration hazard | |
|--------------------------|--|
| No data available | |

| Delayed and immediate effects as well as chronic effects from short and long-term exposure | |
|---|--|
| | |

Trade name: edding OHP-Ink Permanent (green) contained in: edding 140 S, edding 141 F, edding

Current version : 4.2.0, issued: 21.01.2020

Replaced version: 4.1.0, issued: 20.06.2018

Region: GB

Inhalation of vapours may lead to headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.

SECTION 12: Ecological information

12.1 Toxicity

| Toxicity to fish (acute) | | | |
|---------------------------------|---|---------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | ethanol | 64-17-5 | 200-578-6 |
| LC50 | > | 14000 | mg/l |
| Duration of exposure | | 96 | h |
| Species | Pimephales promelas | | |
| Method | EPA E03-05 | | |
| Source | ECHA | | |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |
| 2 | propan-2-ol | 67-63-0 | 200-661-7 |
| LC50 | | 9640 | mg/l |
| Duration of exposure | | 96 | h |
| Species | Pimephales promelas | | |
| Method | OECD 203 | | |
| Source | ECHA | | |

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)

No data available

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No data available

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

| Biodegradability | | | |
|-------------------------|------------------------|----------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | 1-methoxy-2-propanol | 107-98-2 | 203-539-1 |
| Type | aerobic biodegradation | | |
| Value | | 96 | % |
| Duration | | 28 | day(s) |
| Method | OECD 301 E | | |
| Source | ECHA | | |
| Evaluation | readily biodegradable | | |
| 2 | propan-2-ol | 67-63-0 | 200-661-7 |
| Type | BOD/COD | | |
| Value | | 53 | % |
| Duration | | 5 | day(s) |
| Source | ECHA | | |
| Evaluation | readily biodegradable | | |

12.3 Bioaccumulative potential

| Partition coefficient: n-octanol/water | | | |
|---|----------------|---------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | propan-2-ol | 67-63-0 | 200-661-7 |
| log Pow | | 0.05 | |

Trade name: edding OHP-Ink Permanent (green) contained in: edding 140 S, edding 141 F, edding

Current version : 4.2.0, issued: 21.01.2020

Replaced version: 4.1.0, issued: 20.06.2018

Region: GB

| | | |
|-----------------------|------|----|
| Reference temperature | 25 | °C |
| Source | ECHA | |

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

No data available.

12.7 Other information

Other information

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

| | |
|---------------------------|--------|
| Class | 3 |
| Classification code | F1 |
| Packing group | II |
| Hazard identification no. | 33 |
| UN number | UN1263 |
| Proper shipping name | PAINT |
| Special Provision 640 | 640D |
| Tunnel restriction code | D/E |
| Label | 3 |

14.2 Transport IMDG

| | |
|----------------------|----------|
| Class | 3 |
| Packing group | II |
| UN number | UN1263 |
| Proper shipping name | PAINT |
| EmS | F-E, S-E |
| Label | 3 |

14.3 Transport ICAO-TI / IATA

| | |
|----------------------|--------|
| Class | 3 |
| Packing group | II |
| UN number | UN1263 |
| Proper shipping name | Paint |
| Label | 3 |

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

Trade name: edding OHP-Ink Permanent (green) contained in: edding 140 S, edding 141 F, edding

Current version : 4.2.0, issued: 21.01.2020

Replaced version: 4.1.0, issued: 20.06.2018

Region: GB

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

| | |
|---|----------|
| The product is considered being subject to REACH regulation (EC) 1907/2006 annexe XVII. | No 3, 40 |
|---|----------|

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

| | |
|--|-----|
| This product is subject to Part I of Annex I, risk category: | P5b |
|--|-----|

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

Department issuing safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 20335